



# Primary Lithium Battery

## CP332544

3.0V [Li-MnO<sub>2</sub>]

### BENEFITS

- High Voltage Response, Stable During Most of the Lifetime of the Application
- Energy Density up to 830Wh/L
- Wide Operating Temperature Range (-40°C ~+70°C)
- Low Self-discharge Rate (less than 1% per year after 1 year of storage at +25°C)

### KEY FEATURES

- Optimized Battery Structure, Full Discharge Capacity
- Long Endurance
- No Passivation

### MAIN APPLICATIONS

- Security System
- Smart Metering
- RFID and Tracking System
- Wireless Transmitting
- Smart Home Devices
- Military Devices

### References Data

#### Electrical characteristics

Open circuit voltage (at 23±2°C)	3.10V
Nominal capacity	800mAh
(At +25°C, battery discharged at continuous current 1mA until voltage reaches cut-off voltage 2V. The capacity can vary at different temperature, discharge current or cut-off voltage.)	
Maximum continuous current	300mA
(At +25°C, 2.0V cut-off, battery discharged for minimum 50% of rated capacity.)	
Maximum pulse discharge current	500mA
(At +25°C, 2.0V cut-off, battery discharged for minimum 50% of rated capacity with max pulse for 3 seconds after 27 seconds break. The discharged capacity may vary according to the pulse characteristics, the temperature, and the cell's previous history. Fitting the cell with a capacitor may be recommended in severe conditions, consult HCB.)	
Storage (recommended)	+30°C
(For more severe conditions, consult HCB)	
	75%RH
Operating temperature range	-40°C~+70°C
(Operation above ambient Temperature may lead to reduced capacity and lower voltage readings at the beginning of pulses, consult HCB.)	



# Primary Lithium Battery CP332544


3.0V [Li-MnO<sub>2</sub>]

## Physical characteristics

Width	Max25.5mm
Height	Max 44.0mm
Thickness	Max3.3mm
Typical weight	7.2g
Li metal content	0.32g

MSDS as per request  
Diode (1N4007, 1N5819)  
PTC (SRS175...)

Tag, wire, connector, etc. available




Dimensions in mm (GB1804-m)

## WARNING:


- Do Not Short Circuit
- Do Not Recharge
- Do Not Puncture
- Do Not Crush
- Do Not Dismantle
- Do Not Incinerate
- Do Not Mix New and Used Batteries
- Do Not Heat Above 100°C

This information is generally descriptive only and is not intended to make or imply any representation, guarantee or warranty with respect to any cells and batteries. Cell and battery designs/specifications are subject to modification without notice. Contact HCB for the latest information


1. Typical discharge profiles at 23±2°C (at mid-discharge)



2. Voltage plateau versus Current and Temperature (at discharge stable phase)



3. Storage characteristics



## HCB BATTERY CO., LTD

Add: 37 Tianyuan Street, Dongxihu District, Wuhan, Hubei, China

P.O.: 430040

Tel: +86(0)27 83248452

Fax: +86(0)27 83248455

Email: haocheng@cnhcb.com

Web: www.cnhcb.com

No.: HCB-MKT.PM-S[V2.3 2024 04]